

. . .

LED candle

RGB-W & flame / DMX-HF













Diameter 10cm 3 heights 22/30/42 cm

Possibility of using candlesticks to multiply the heights





. . .





Adjustable flickering flame



RGB+White Candle body

Contactless induction charging











Induction Flight-case 24 candles


No connector, OBELIE engraved and customizable flight case (+customer logo, cups, plates)





DMX-HF control





DMX panel + DMX transmitter



• Channel 1: Dimmer flame

• Channel 2: Dimmer candle RGB-W

• Channel 3: Flickering

0-> 50% Flame flickering only

50-> 100% Flame & under-flame flickering

• Channel 4: Red candle

• Channel 5: Green candle

• Channel 6: Blue candle

• Channel 7: White candle


• Channel 8: Switching ON/OFF each level of the candle

0-> 50%: switching ON level 1, then 1 & 2, etc

50-> 100%: switching OFF level 1, then 1 & 2, etc










Technical features

- Flame Lighting
- RGB-W lighting (candle)
- Flickering (flame + under flame)
- LiFePO4 battery: Stable, cobalt-free and >2000 cycles
- Autonomy* > 6h30 to 15 days
- Charging by induction in flight case without connector
- DMX-HF control via DMX panel+ DMX transmitter
- Assignment by groups or individually
- IP64 waterproofing

*Autonomy for candle size 30 cm & 32 LEDs









CSR policy inside

LOCAL Design & assembly in France

INCLUSION Disabled people for assembly (E.A.)

DURABLE Battery > 2000 cycles

ECO-DESIGN Reparaible product

RECYCLABLE Recyclable cobalt-free batteries


ETHICS No questionable extraction sector (cobalt)















JEU DE LUMIÈRE SANS FIL

JEU DE LUMIERE SANS FIL

